Unique Design Features

- Pre insulated, plug and play unit.
- Compact pre-wiredunit, with control panel and pump mounted on it.
- Calorifier (Optional) instead of direct mixing tank ensures instant start up and dispenses with the requirement for softener on primary circuit.
- Easy to operate and maintain.

Applications



Hotel










Insulated

Helical · Monobloc 4

Technical Specifications

Description	Unit	AMW 005	AMW 01	AMW 02	AMW 03	AMW 04	AMW 06	
Capacity	kcal / hr	50000	100000	200000	300000	400000	600000	
Maximum Outlet Temperature	°C	90						
Water Flow Rate	m³ / hr	4	9	12	18	20	30	
Temperature Difference (△t)	°C	13	11	17	17	20	20	
Efficiency	As Per BS 845 Part 1 NCV Basis							
Diesel (HSD)	%	% 93						
Gas (NG / LPG)	%	% 92.5						
Fuel	HSD / LPG / NG							
Fuel Firing System	Pressure Jet, Mono-Bloc							
Fuel Consumption								
HSD	kg / hr	5.12	10.24	20.48	30.72	40.96	61.44	
NG	Nm³ / hr	6.36	12.72	25.44	38.16	50.87	76.31	
LPG	Nm³ / hr	2.17	4.33	8.67	13.00	17.34	26.01	
Connected Electrical Load								
HSD / NG / LPG	kW	1.53	2.33	3.08	4.95	5.15	7.30	
Dimensions & Weight	Without Calorifier							
LxWxH	m	1.07x0.95x0.91	1.33x1.25x1.92	1.5x4.2x1.97	2.25x2.6x2.25	2.24x1.38x2.23	2.81x1.55x2.51	
Dry Weight	kg	500	875	899	1500	1500	2270	
Dimensions & Weight	With Calorifier							
LxWxH	m	1.2x2.08x1.7	1.94x2.12x1.9	1.55x2.33x1.95	2.25x2.60x2.25	2.25x2.70x2.41	2.81x3.07x2.67	
Dry Weight	kg	1175	1550	1900	3100	3100	3566	
Chimney Top Diameter	mm	150	200	200	250	250	250	

Note: Efficiency is calculated based on NCV of Diesel as 10500 kcal/kg, LPG as 24940 kcal/Nm3 and Natural Gas as 8500 kcal/Nm3. Above mentioned weight and dimensions connected load may vary with actuals. Please refer





Sustainable Solutions in **Energy & Environment**

www.thermaxglobal.com

Registered Office

D-13, MIDC Industrial Area, R D Aga Road, Chinchwad, Pune 411019, India

enquiry@thermaxglobal.com

Customer Care: 1800-209-0115

shorturl.at/fyFMS f shorturl.at/RSWX7





in shorturl.at/ctzSX shorturl.at/dBZ05

Thermax Business Portfolio

- Heating
- Cooling
- Power
- Air Pollution Control
- Chemicals
- Water and Wastewater Solutions
- Solar
- Specialised Services



AQUAMATIC[™]

Compact & Instant Hot Water Generator



Heating Business

Improving your business is our business

Thermax is an engineering major providing sustainable solutions in the areas of energy and environment. Spanning over 86 countries, clients make use of Thermax's business-tobusiness solutions for heating, cooling, power and cogeneration plants; waste heat recovery units; systems for water & wastewater management and air pollution control; performance improving chemicals.

Thermax's operations are supported by ongoing Research & Development, tie-ups with global technology majors, an international sales & service network spread over 27 countries and state-of-the-art manufacturing facilities in 14 locations including India, China, Poland Indonesia, Denmark and Germany.

As a part of Thermax heating business, Process Heating solutions, a strategic business unit offers packaged boilers, thermal oil heaters, heat recovery boilers and hot water generators. Innovated by a strong R&D that focuses on customer applications, we offer a range of heating systems designed to burn fuels including biomass and heavy liquid fuels. We have installations in various parts of the world. Oil & gas based systems in Middle East and Europe, biomass and solid fuel fired equipment in South East Asia and Africa. Heating business specializes in bringing life to the most innovative product ranges catering the majority of industries across the Globe.