

MAXFLEX[®] PU PR

Primer for Polyurethane Sealant

Maxflex[®] PUPR is a specially developed product to enhance the bonding of polyurethane sealant Maxflex[®] PU with the porous substrates such as cement, concrete, wood, asbestos, stones, bricks etc.

Benefits

- Easily applicable by brush
- Due to its low viscosity it penetrates deeply into the substrate
- Enhances the bonding of sealant with substrates
- It remains unaffected by UV rays and weathering conditions.

Properties

Nature	Single Component, Moisture Sensitive Liquid
Colour	Pale Yellow to Light Brown
Specific Gravity at 30°C	1.00±0.05
Viscosity on Ford Cup B4	12-18 sec
Intercoat Interval	15-20 minutes
Sealant Application Time	30 minutes after the application of primer
Number of Coats Required	2

Instructions for Use

Clean the surface with brush and ensure no loose particle remains on the substrate. Clean the substrate with solvents if any oil or grease particles are there. On the clean and dry substrate apply Maxflex[®] PUPR with a standard paintbrush at the rate of 50-60 sq. ft. / lit/ coat.

Cleaning

Un-dried primer can be removed with solvents like xylene, toluene or acetone. Dried primer has to be scrapped off.

Health and Safety Instructions

Maxflex[®] PUPR is flammable keep away from source of ignition and fire.

Storage

In order to preserve all the properties, store the material in the original unopened containers in containers in cool and dry place.


Shelf Life

The shelf life of Maxflex[®] PUPR is 12 months from the date of manufacturing if stored as per the above storage conditions.

Packing

250 ml





THERMAX

Thermax Limited
Environment House, Plot No.90-92
BG Block, MIDC, Bhosari,
Pune 411 026, India.
Tel: +91-20-67156000
Fax: +91-20-27120206
Customer Care: 18002090115 (India
toll free)
Email : enquiry@thermaxglobal.com

Ahmedabad

Tel: +91-79-26575408 • Fax: +91-79-65577270

Bengaluru

Tel: +91-80-22371721 • Fax: +91-80-22371726

Chennai

Tel: +91-44-24303400 • Fax: +91-44-24353841

Delhi

Tel: +91-11- 46087200 • Fax: +91-11- 26145311

Hyderabad

Tel: +91-40-23253700 • Fax: +91-40-23253799

Kolkata

Tel: +91-33-66070800 • Fax: +91-33-66070999

Mumbai

Tel: +91-22-67542222 • Fax: +91-22-22040859

Thermax World-wide

UK, USA, UAE, Germany, Belgium, Denmark,
Russia, Saudi Arabia, Thailand, Malaysia,
Bangladesh, Sri Lanka, China, Philippines,
Peru, Chile, Kenya, Nigeria, Brazil, Indonesia

Website: www.thermaxglobal.com

Thermax Business Portfolio

Chemicals

Absorption Cooling

Air Pollution Control

Boilers &Heaters

Power

Water & Waste Solutions

Solar

Other Segments:

- Concrete Admixtures • Surface Treatments • Grouts & Anchors • Repair & Rehabilitation
- Protective Coatings • Industrial Flooring • Waterproofing • Sealants • Adhesives

Disclaimer: The information contained in this document is true and accurate to the best of our knowledge and is based on our experience & test results. It is always the Company's endeavor to give true and accurate information however as it does not have any direct and/or continuing control on the use of the Products, the Company cannot accept any liability, direct or indirect as a consequence of the use of Products. In the event of any doubt upon any critical parameter it is advisable to seek clarification from our technical representative.