

MAXTREAT[®] CF

Single Part, Non-Shrink, Cementitious Crack Sealer for Plaster, Masonry and Concrete



Maxtreat[®] CF is a crack sealing cementitious material in powder form. It is easy to apply and can be finished or smoothed off with a putty blade or a damp sponge. It sets quickly on application and can be over coated with common paints / coatings.

Uses

Maxtreat[®] CF is used for sealing cracks on plaster, masonry and concrete substrates.

Benefits

- **Single Component-** Easy to use
- **Versatile-** Can be used for plaster, masonry or concrete, can be painted after application
- **Non Sagging-** Can be used for horizontal, vertical and overhead applications
- **Good Adhesion-** Effective bonding with substrate
- **Non Shrink-** Shrinkage cracking eliminated

Properties

Colour	White
Setting Time	15-20 minutes
Compressive Strength (ASTM C 109)	22 N/mm ² in 7 days 24 N/mm ² in 28 days
Mix Density	1.88-1.98 gm/cc
W/P Ratio	0.36
Mix Proportions by Volume	1 Part Water : 2.5-3 Parts of Powder
Minimum Application Temperature	10°C

Instructions for Use

Surface Preparation

The cracks to be sealed shall be saw cut or chiselled to form a 'V' groove of approximately of 6mm x 6mm. The grooves shall be cleaned to remove all the loose particles, dust, etc. The groove shall be sprinkled with clean water before applying the sealing mortar.

Mixing

Maxtreat[®] CF shall be mixed with water adopting w/p ratio 0.36 by weight or a mix proportion of 1 part of water to 2.5-3.0 parts of Maxtreat[®] CF, by volume.

Thorough mixing shall be carried out till a smooth, homogenous paste is obtained.

Application

The mixed paste is filled into the groove by gloved hand and the surface finished using a putty blade. This is continued till the full length of crack is sealed.

Curing

Curing is necessary only when groove size exceeds 6mmwidth or in areas exposed to UV.

Cleaning

Tools may be cleaned with clean water as Maxtreat[®] CF is a cement based product.

Limitations

Maxtreat[®] CF crack sealer cannot be used for moving cracks and for crack width greater than 30mm.

Health & Safety Instructions

Maxtreat[®] CF has no health hazards in normal use. Gloves shall be worn while mixing and during application. Splashes of material to the eyes shall be washed off with clean water. In the event of prolonged irritation, medical advice shall be sought.

Fire

Maxtreat[®] CF is non-flammable.

Storage

Shelf Life


Maxtreat[®] CF has a shelf life of 6 months in original unopened packs if stored in unopened conditions below 35°C.

Packing

Maxtreat[®] CF is supplied in 1 and 5 kg bag.

Coverage

25 m per kg for a V groove crack of 6mm x 6mm. The actual coverage may vary depending on the substrate conditions.



THERMAX

Thermax Limited
Environment House, Plot No.90-92
BG Block, MIDC, Bhosari,
Pune 411 026, India.
Tel: +91-20-67156000
Fax: +91-20-27120206
Customer Care: 18002090115 (India
toll free)
Email : enquiry@thermaxglobal.com

Ahmedabad

Tel: +91-79-26575408 • Fax: +91-79-65577270

Bengaluru

Tel: +91-80-22371721 • Fax: +91-80-22371726

Chennai

Tel: +91-44-24303400 • Fax: +91-44-24353841

Delhi

Tel: +91-11- 46087200 • Fax: +91-11- 26145311

Hyderabad

Tel: +91-40-23253700 • Fax: +91-40-23253799

Kolkata

Tel: +91-33-66070800 • Fax: +91-33-66070999

Mumbai

Tel: +91-22-67542222 • Fax: +91-22-22040859

Thermax World-wide

UK, USA, UAE, Germany, Belgium, Denmark,
Russia, Saudi Arabia, Thailand, Malaysia,
Bangladesh, Sri Lanka, China, Philippines,
Peru, Chile, Kenya, Nigeria, Brazil, Indonesia

Website: www.thermaxglobal.com

Thermax Business Portfolio

Chemicals

Absorption Cooling

Air Pollution Control

Boilers & Heaters

Power

Water & Waste Solutions

Solar

Other Segments:

- Concrete Admixtures • Surface Treatments • Grouts & Anchors • Repair & Rehabilitation
- Protective Coatings • Industrial Flooring • Waterproofing • Sealants • Adhesives

Disclaimer: The information contained in this document is true and accurate to the best of our knowledge and is based on our experience & test results. It is always the Company's endeavor to give true and accurate information however as it does not have any direct and/or continuing control on the use of the Products, the Company cannot accept any liability, direct or indirect as a consequence of the use of Products. In the event of any doubt upon any critical parameter it is advisable to seek clarification from our technical representative.