

# TECFLOOR<sup>®</sup> PR

## Epoxy Resin Based Primer for Concrete Surfaces



Tecfloor<sup>®</sup> PR is a solvent free two component epoxy based primer with good penetrating properties for concrete surfaces.

### Uses

Tecfloor<sup>®</sup> PR is suitable for priming concrete surfaces prior to the application of any of the Tecfloor<sup>®</sup> ET 1000-4000, EC/ES range of resin based floor toppings, T-Guard range of epoxy protective coatings and epoxy mortars

### Benefits

- Can be applied even on damp surfaces.
- Improves the adhesion of epoxy floor toppings and mortars with the substrate.

### Technical support

Thermax provides a countrywide technical advisory service supported by a team of specialists in the field.

### Properties

Pot Life @ 27°C	25-30 minutes
Mixed Density @ 25°C	1.15-1.17 kg/l
Adhesive Bond Strength with Concrete	4 N/mm <sup>2</sup> (ASTM D 4541)

### Instructions for use

#### Surface Preparation

Thorough surface preparation is vital. For best results Thermax recommends mechanical scarifying, grit blasting, sand blasting, etc. For flooring and tanking works, care must be taken to ensure that the substrate does not suffer from rising dampness. If such conditions exist, consult Thermax.

#### New concrete floors

Should be at least 28 days old or have a moisture content of less than 5% before proceeding with epoxy application. Laitance and deposits on new concrete floors are best removed by light grit blasting, mechanical scrubbing or grinding. On smaller areas thorough etching using etching agent may be considered. After etching, the floor should be thoroughly washed with clean water and then allowed to dry.

#### Old concrete floors

Again, mechanical cleaning methods are strongly recommended on old concrete floors, particularly where heavy contamination by oil and grease has occurred or existing coatings are present. These may well have been absorbed several millimeters deep into the concrete. To ensure good adhesion all contamination should be removed and the surface

#### Limitations

Recommended application temperature range is 10°C to 40°C. Thermax shall be consulted where application or service temperature is outside this range.

#### Health & Safety Instructions

Tecfloor<sup>®</sup> PR should not come into contact with skin and eyes or be swallowed.

Some people are sensitive to epoxy resins, hardeners and solvents. Gloves, goggles and barrier creams should therefore be used while handling the product. Adequate ventilation should be ensured and if working in enclosed areas, suitable breathing apparatus must be used. If the resin comes in contact with skin, it must be removed before it hardens with a resin removing cream, followed by washing with soap and water solvent should not be used.

Cleaning Sol should be washed from skin immediately with soap and water. Should accidental eye contamination occur with any of the above products, it should be washed well with plenty of water and medical advice should be sought. If swallowed medical attention should be sought immediately. Vomiting should not be induced.

#### Cleaning

All tools and equipments should be cleaned with solution immediately after use. Spillages should be absorbed with sand or sawdust and disposed off in accordance with local regulations

#### Fire

Cleaning sol, Tecfloor<sup>®</sup> PR are flammable. Do not expose to naked flames or other sources of ignition. Do not smoke while handling the material. Containers should be tightly sealed when not in use. In the event of fire, extinguish with CO<sup>2</sup> or foam type extinguishers.

# TECFLOOR® PR

## Flash Point

Cleaning Solution- 33°C  
Tecfloor® PR- 25°C

## Storage

Tecfloor® PR has a shelf life of 12 months when stored in unopened containers under normal warehouse conditions.

## Packing

Tecfloor® PR is available in 1 and 4 litre packs.

## Coverage


Approximate coverage rate: 5.5-6.5 m<sup>2</sup>/ltr

## Other Segments:

- Concrete Admixtures • Surface Treatments • Grouts & Anchors • Repair & Rehabilitation
- Protective Coatings • Industrial Flooring • Waterproofing • Sealants • Adhesives

**Disclaimer:** The information contained in this document is true and accurate to the best of our knowledge and is based on our experience & test results. It is always the Company's endeavor to give true and accurate information however as it does not have any direct and/or continuing control on the use of the Products, the Company cannot accept any liability, direct or indirect as a consequence of the use of Products. In the event of any doubt upon any critical parameter it is advisable to seek clarification from our technical representative.

We reserve the right to amend any product details without notice. Copyright © Thermax Limited Edition: (TCC/TDS/0320)



**THERMAX**

Thermax Limited  
Environment House, Plot No.90-92  
BG Block, MIDC, Bhosari,  
Pune 411 026, India.  
Tel: +91-20-67156000  
Fax: +91-20-27120206  
Customer Care: 18002090115 (India  
toll free)  
Email : [enquiry@thermaxglobal.com](mailto:enquiry@thermaxglobal.com)

### Ahmedabad

Tel: +91-79-26575408 • Fax: +91-79-65577270

### Bengaluru

Tel: +91-80-22371721 • Fax: +91-80-22371726

### Chennai

Tel: +91-44-24303400 • Fax: +91-44-24353841

### Delhi

Tel: +91-11- 46087200 • Fax: +91-11- 26145311

### Hyderabad

Tel: +91-40-23253700 • Fax: +91-40-23253799

### Kolkata

Tel: +91-33-66070800 • Fax: +91-33-66070999

### Mumbai

Tel: +91-22-67542222 • Fax: +91-22-22040859

### Thermax World-wide

UK, USA, UAE, Germany, Belgium, Denmark,  
Russia, Saudi Arabia, Thailand, Malaysia,  
Bangladesh, Sri Lanka, China, Philippines,  
Peru, Chile, Kenya, Nigeria, Brazil, Indonesia

Website: [www.thermaxglobal.com](http://www.thermaxglobal.com)

## Thermax Business Portfolio

### Chemicals

### Absorption Cooling

### Air Pollution Control

### Boilers &

### Heaters Power

### Water & Waste Solutions

### Solar